

Our EZ Street Hose Ends are the perfect solution for the automotive enthusiast looking to upgrade their fuel system with aftermarket hose and hose ends. They have been designed to be used with today's pump gas. E85, E98, Diesel, Methanol, or other Ethanol Blends.

Features

- Manufactured in Southington, Connecticut with a single hose retention barb made to SAE specifications.
 This allows this series hose ends to work on virtually any SAE 30R9 or 30R10 Low Permeation Fuel Hose, (Including our New EZ Street 30R9 Hose).
- Black bright dip anodized for good looks and long lasting protection.
- · Double-swivel design allows for clocking during installation.
- Available in standard size -6 AN, (3/8") and -8 AN, (1/2") for higher horsepower applications.

Need to convert from a standard 5/16" barb to -6AN on your stock tank? Use our P/N 484205BL to ease installation.



Straight Size 6 AN, 3/8" 8 AN, 1/2"	Part No. 750106BL 750108BL	90 Degree Size 6 AN, 3/8" 8 AN, 1/2"	Part No. 759006BL 759008BL
30 Degree Size 6 AN, 3/8" 8 AN, 1/2"	Part No. 753006BL 753008BL	120 Degree Size 6 AN, 3/8" 8 AN, 1/2"	Part No. 751206BL 751208BL
45 Degree Size 6 AN, 3/8" 8 AN, 1/2"	Part No. 754506BL 754508BL	150 Degree Size 6 AN, 3/8" 8 AN, 1/2"	Part No. 751506BL 751508BL
60 Degree Size 6 AN, 3/8" 8 AN, 1/2"	Part No. 756006BL 756008BL	180 Degree Size 6 AN, 3/8" 8 AN, 1/2"	Part No. 751806BL 751808BL

Assembly couldn't be easier. Simply cut the hose to length using a razor blade or our Rubber Hose Cutter P/N 900066. Push the Hose over the hose barb and secure with one of our Push Lock Hose Clamps or the appropriate worm gear or EFI style clamp.



escription	Part No.
liers	999150
6 AN Clamps, Pair	999156
B AN Clamps. Pair	999158



Our new series of EZ Street Low Permeation Fuel Hose is made to SAE 30R9 Specifications.

Compatible with all of today's pump gas, our new EZ Street Hose will be right at home on your car using E85, E98, Diesel, Methanol, or other Ethanol Blended Fuels.

The Hose features a Nitrile based tube that prevents 99% of hydrocarbon fuel vapors from escaping. This drastically reduces fuel odors over standard synthetic rubber hose used in the automotive racing industry.

It also features an Aramid Reinforcing Braid that keeps the hose from collapsing while routing through the car and it makes it suitable for use in both carbureted and fuel injected applications up to 175 PSI.

Available in standard size -6 AN, (3/8") and -8 AN, (1/2") for higher horsepower applications.

SIZE	LENGTH	PART NO.
-6AN, 3/8"	BULK	730006
-8AN, 1/2"	BULK	730008
-6AN, 3/8"	3 FEET	733006
-8AN, 1/2"	3 FEET	733008
-6AN, 3/8"	6 FEET	736006
-8AN, 1/2"	6 FEET	736008
-6AN, 3/8"	10 FEET	731006
-8AN, 1/2"	10 FEET	731008
-6AN, 3/8"	15 FEET	731506
-8AN, 1/2"	15 FEET	731508
-6AN, 3/8"	20 FEET	732006
-8AN, 1/2"	20 FEET	732008

