

RACE-RITE CRIMP-ON HOSE ENDS

Fragola's New "Double-Swivel" Race-Rite, Crimp-on Hose Ends have a Hard Coat Black finish. They feature an enlarged I.D. for improved flow rates and utilize a unique thread-on collar. The collar threads onto the Hose End Body and ensures a concentric crimp every time. And because they are a "Double-Swivel" design, there is no need worry about clocking them into the proper orientation before crimping. Use with our Race-Rite & Race-Rite Pro Hose.



STRAIGHT HOSE ENDS Hose Size Part No. -4 2600104 -6 2600106 2600108 -8 -10 2600110 -12 2600112 2600116



30º HO	SE ENDS
Hose	
Size	Part No.
-4	2603004
-6	2603006
-8	2603008
-10	2603010
-12	2603012
-16	2603016



45° HOSE ENDS Hose Size Part No. 2604504 2604506 -6 -8 2604508 -10 2604510 -12 2604512 2604516



60º HOSE ENDS Hose Size Part No. 2606004 -4 -6 2606006 -8 2606008 2606010 -10 -12 2606012 -16 2606016



90° HOSE ENDS Hose Part No. Size 2609004 -4 -6 2609006 2609008 -8 -10 2609010 -12 2609012 2609016



120º H	OSE ENDS
Hose	
Size	Part No.
-4	2612004
-6	2612006
-8	2612008
-10	2612010
-12	2612012
-16	2612016



150° HOSE ENDS Hose Size Part No. 2615004 -4 2615006 -6 -8 2615008 2615010 -12 2615012 2615016



180° HOSE ENDS Hose Part No. Size -4 2618004 -6 2618006 -8 2618008 -10 2618010 2618012 -12 -16 2618016

RACE-RITE DIRECT FIT CRIMP-ON HOSE ENDS

Race-Rite Direct Fit Crimp-On Hose Ends come in handy when plumbing jobs in tight spaces. They incorporate a "swivel-style" O-ring Boss fitting into their design, which helps shave valuable inches in tight applications.



30° HOSE ENDS

Hose Size Thread -10 7/8-14 (10) -12 1 1/16-12 (12)

Part No. 2603010RAD 2603012RAD



45° HOSE ENDS

Hose Size **Thread** -10 7/8-14 (10) -12 1 1/16-12 (12)

Part No. 2604510RAD 2604512RAD



60º HOSE ENDS

Hose Size -10

-12

Thread 7/8-14 (10) 1 1/16-12 (12)

Part No. 2606010RAD 2606012RAD



90º HOSE ENDS

Hose Size Thread 7/8-14 (10) -10 1 1/16-12 (12)

Part No. 2609010RAD 2609012RAD



Part No.

2612010RAD

2612012RAD

120° HOSE ENDS

Hose Size **Thread** 7/8-14 (10) -10 -12 1 1/16-12 (12)



150° HOSE ENDS

Hose Size Thread 7/8-14 (10) -10 -12 1 1/16-12 (12)



Part No.

2615010RAD

2615012RAD

180º HOSE ENDS

Hose Size **Thread** 7/8-14 (10) -10 -12 1 1/16-12 (12)

Part No. 2618010RAD 2618012RAD

RACERITE & RACERITE PRO HOSE The Last Hose Upgrade Your Race Car Will Ever Need!

Fragola Performance Systems

RaceRite Hose

Desc.	Hose	Hose	Bulk	3 FT.	6 FT.	10 FT.	15 FT.	20 FT.
(ln.)	I.D.	O.D.	Per FT.	Roll	Roll	Roll	Roll	Roll
#4	1/4"	.360"	2700004	2700304	2700604	2701004	2701504	2702004
#6	3/8"	.520"	2700006	2700306	2700606	2701006	2701506	2702006
#8	1/2"	.655"	2700008	2700308	2700608	2701008	2701508	2702008
#10	5/8"	.820"	2700010	2700310	2700610	2701010	2701510	2702010
#12	3/4"	.950"	2700012	2700312	2700612	2701012	2701512	2702012
#16	1"	1.25"	2700016	2700316	2700616	2701016	2701516	2702016

Race-Rite Hose

- · The ultimate Fuel, ATF & Coolant hose
- Smoothbore Conductive P.T.F.E. Core is Resistant to Fuel Permeation
- Convoluted Exterior allows for tighter bend radius
- 60% Lighter than our Black Nylon Race hose
- Features a true to Size I.D. for improved flow rate
- Works with all fluids, including Ethanol Type Fuels, ATF, Coolant & Oils
- Use with our Race-Rite Crimp-on Hose Ends
- Operating range -65° 500° F

TECHNICAL SPECIFICATIONS

Part	AN	Working	Vacuum	Minimum	Weight
Number	Size	Pressure	Rating	Bend Radius	Per FT.
2700004	#4	900 PSI	28 in HG	1-1/2"	.04 lbs.
2700006	#6	800 PSI	28 in HG	2"	.07 lbs.
2700008	#8	600 PSI	28 in HG	3"	.09 lbs
2700010	#10	500 PSI	28 in HG	4"	.14 lbs.
2700012	#12	420 PSI	28 in HG	5"	.16 lbs.
2700016	#16	400 PSI	28 in HG	6"	.24 lbs.

RaceRite Pro Hose

- Engineered & tested to be the ideal plumbing solution in all Dry Sump System applications
- Convoluted exterior with added Spiral Wire increases hoop strength to prevent hose sucking shut under high vacuum & allows for an even tighter bend radius
- 50% lighter than our 8400 Series Black Nylon Race Hose.
- Features a true to size I.D. for improved flow rate.
- . Works with all fluids including Ethanol Type Fuels, ATF, Coolant, & Oils
- Use with our Race-Rite Crimp-on Hose Ends
- Operating Range -65°-500° F

RaceRite Pro Hose

Desc.	Hose	Hose	Bulk	3 FT.	6 FT.	10 FT.	15 FT.	20 FT.	
(ln.)	I.D.	O.D.	Per FT.	Roll	Roll	Roll	Roll	Roll	
#6	3/8"	.520"	2710006	2710306	2710606	2711006	2711506	2712006	
#8	1/2"	.655"	2710008	2710308	2710608	2711008	2711508	2712008	
#10	5/8"	.820"	2710010	2710310	2710610	2711010	2711510	2712010	
#12	3/4"	.950"	2710012	2710312	2710612	2711012	2711512	2712012	
#16	1"	1.25"	2710016	2710316	2710616	2711016	2711516	2712016	

FT. oil 2006 2008 2010 2012 2016

TECHNICAL SPECIFICATIONS

Part	AN	Working	Vacuum	Minimum	Weight
Number	Size	Pressure	Rating	Bend Radius	Per FT.
2710006	#6	1160 PSI	28 in HG	1"	.08 lbs.
2710008	#8	1015 PSI	28 in HG	1-1/2"	.12 lbs.
2710010	#10	940 PSI	28 in HG	1-3/4"	.17 lbs.
2710012	#12	870 PSI	28 in HG	2-1/4"	.21 lbs.
2710016	#16	725 PSI	28 in HG	3"	.33 lbs.

For more information call us @ (866) 337-2739 or visit www.FragolaPerformanceSystems.com